



# SONIC<sup>®</sup> CHAIN OIL

LIGHT, MEDIUM, HEAVY

## PRODUCT DESCRIPTION

SONIC<sup>®</sup> CHAIN OILS are blended to produce a very tacky product that will adhere extremely well (reducing throw-off and dripping) to the guide bar and chain of power saws.

## PERFORMANCE FEATURES

- Tackiness agents enable the oil to maintain a protective oil film to lubricate the chain and bar
- Anti-wear additives protect against premature wear of the metal components
- Anti-rust protection resists water corroding metal parts
- Provides good flow ability at all temperatures (three weights are available)

## APPLICATIONS

SONIC<sup>®</sup> CHAIN OILS are recommended for use in the chain-oil reservoir on a majority of modern chainsaws. Their tacky nature and proprietary formulation protect the guide bar and chain from excessive wear. They can be used as a basic chain lubricant for applications that require hand rolling and for lubricating guide bars.

SONIC<sup>®</sup> CHAIN OILS are blended in three specific grades to cover all seasons:

- Light = Winter applications
- Medium = Shoulder season applications (spring and fall)
- Heavy = Summer applications

## TECHNICAL PROPERTIES

The values listed below are typical of current production. As variations may occur, these numbers do not constitute a specification.

PROPERTIES	TEST METHODS	LIGHT	MEDIUM	HEAVY
Kinematic Viscosity cSt @ 40°C	ASTM D445	59.0	105.0	164.0
Kinematic Viscosity cSt @ 100°C	ASTM D445	8.9	11.6	16.3
Viscosity Index	ASTM D2270	137	97	103
Pour Point, °C	ASTM D97	-45°	-27°	-24°

## PRODUCT SELECTION

Product availability can vary by location. Please contact your local retail co-op for further details.

PRODUCT SIZES	LIGHT	MEDIUM	HEAVY
1 L Bottle		✓	
5 L Bottle	✓		✓
10 L Bottle			
20 L Pail			
110 L Drum			
205 L Drum	✓		✓
1000 L Tote	✓		✓

## MATERIAL SAFETY DATA SHEETS

Product-specific material safety data sheets (MSDS) can be obtained by contacting your local retail co-op or Federated Co-operatives Limited (see contact information below) or by going online at [coopconnection.ca](http://coopconnection.ca)

## RECYCLING OF USED LUBRICANTS AND CONTAINERS

Please protect the environment when disposing of petroleum products. All products should be taken to an authorized collection facility or picked up by a qualified organization. This ensures the products will be disposed of in an environmentally sensitive manner. For additional information on used-oil recycling programs, please see the following:

- Saskatchewan – [www.usedoilrecyclingsk.com](http://www.usedoilrecyclingsk.com)
- Alberta – [www.usedoilrecyclingab.com](http://www.usedoilrecyclingab.com)
- British Columbia – [www.bcusedoil.com](http://www.bcusedoil.com)
- Manitoba – [www.usedoilrecycling.com/en/mb](http://www.usedoilrecycling.com/en/mb)

## CONTACT INFO

For more information on this or any other CO-OP<sup>®</sup> lubricant product, please contact your local retail co-operative or Federated Co-operatives Limited.

[petroadmin@fcl.crs](mailto:petroadmin@fcl.crs) • [www.fuel.crs](http://www.fuel.crs) • [www.agro.crs](http://www.agro.crs)

SONIC<sup>®</sup> <sup>®</sup>Registered trademark of Federated Co-operatives Limited, Saskatoon S7K 3M9

<sup>®</sup> CO-OP and the CO-OP logo are registered trademarks of TMC Distributing Ltd., Saskatoon S7K 3M9



**PREMIUM  
LUBRICANTS**