



# SONIC<sup>®</sup> DYNAMIX PLUS<sup>®</sup>

SYNTHETIC BLEND UNIVERSAL TWO-CYCLE ENGINE OIL

## PRODUCT DESCRIPTION

SONIC DYNAMIX PLUS<sup>®</sup> is a high quality synthetic blend universal two-cycle engine oil. The premium ashless formula provides exceptional lubricity, to reduce engine wear and extend engine life. It's advanced formula is an exceptional choice for both direct injection and pre-mix engines.

## PERFORMANCE FEATURES

- High temp oxidation control
- Extended engine life
- Reduced engine deposits
- Controls piston and cylinder scuffing
- Excellent rust and corrosion protection
- Improved light throttle operation
- Balanced formula reduces exhaust smoke

## APPLICATIONS

SONIC DYNAMIX PLUS<sup>®</sup> is recommended for use in two-cycle outboard engines, personal watercraft, ATV's, low output chainsaws, weed trimmers and leaf blowers. It works in most water-cooled and air-cooled applications and is designed to meet the high performance requirements of major outboard engine manufacturers including Mercury, Mariner, Johnson, Evinrude, Yamaha and Suzuki.

*\*Do not use in Orbital or Ficht designed engines.*

## TECHNICAL PROPERTIES

The values listed below are typical of current production. As variations may occur, these numbers do not constitute a specification.

PROPERTIES	TEST METHODS	SONIC <sup>®</sup> DYNAMIX PLUS <sup>®</sup>
Kinematic Viscosity cSt @ 40°C	ASTM D445	43.9
Kinematic Viscosity cSt @ 100°C	ASTM D445	8.1
Viscosity Index	ASTM D2270	160
Pour Point, °C	ASTM D97	-45°
Brookfield Viscosity cP @ -25°C	ASTM D2983	3,439

## PERFORMANCE SPECIFICATIONS

In the appropriate grade, SONIC DYNAMIX PLUS® is approved and/or recommended for use in the following:

INDUSTRY / OEM	SPECIFICATIONS
API	TC
JASO	FB
NMMA	TC-W3 / TC-WII™ / TC-W™

## MATERIAL SAFETY DATA SHEETS

Product-specific material safety data sheets (MSDS) can be obtained by contacting your local retail co-op or Federated Co-operatives Limited (see contact information below) or by going online at [coopconnection.ca](http://coopconnection.ca)

## PRODUCT SELECTION

Product availability can vary by location. Please contact your local retail co-op for further details.

PRODUCT SIZES	SONIC® DYNAMIX PLUS®
1 L Bottle	✓
5 L Bottle	✓
10 L Bottle	
20 L Pail	
110 L Drum	
205 L Drum	
1000 L Tote	

## RECYCLING OF USED LUBRICANTS AND CONTAINERS

Please protect the environment when disposing of petroleum products. All products should be taken to an authorized collection facility or picked up by a qualified organization. This ensures the products will be disposed of in an environmentally sensitive manner. For additional information on used-oil recycling programs, please see the following:

- Saskatchewan – [www.usedoilrecyclingsk.com](http://www.usedoilrecyclingsk.com)
- Alberta – [www.usedoilrecyclingab.com](http://www.usedoilrecyclingab.com)
- British Columbia – [www.bcusedoil.com](http://www.bcusedoil.com)
- Manitoba – [www.usedoilrecycling.com/en/mb](http://www.usedoilrecycling.com/en/mb)

## CONTACT INFO

For more information on this or any other CO-OP® lubricant product, please contact your local retail co-operative or Federated Co-operatives Limited.

[petroadmin@fcL.crs](mailto:petroadmin@fcL.crs) • [fuel.crs](mailto:fuel.crs) • [agro.crs](mailto:agro.crs)

SONIC® DYNAMIX PLUS® ®Registered trademark of Federated Co-operatives Limited, Saskatoon S7K 3M9  
®CO-OP and the CO-OP logo are registered trademarks of TMC Distributing Ltd., Saskatoon S7K 3M9

