



SONIC[®] AR – DRILL OIL

EP LUBRICANT FOR AIR-OPERATED ROCK DRILLS AND TOOLS

PRODUCT DESCRIPTION

SONIC[®] AR-DRILL OIL is an extreme-pressure lubricant formulated to both cool and lubricate pneumatic tools such as rock drills and jackhammers. AR-DRILL OILS contain extreme pressure (EP) and corrosion protection additives to ensure equipment protection. AR-DRILL OILS are blended in two specific grades: ISO 46 and ISO 100. Within the line, the most diverse grade is the ISO 100.

APPLICATIONS

SONIC[®] AR-DRILL OIL is recommended for use by grade in a wide range of pneumatic equipment such as these:

- Rock drills
- Jackhammers
- Drifters
- Wagon drills
- Tampers
- Impact tools
- Pavement breakers

PERFORMANCE FEATURES

- Meets the lubricant demands of pneumatic equipment requiring extreme-pressure protection
- Extreme-Pressure (EP) formulation helps prevent premature damage and wear to hardened steel parts
- Protects internal parts from rust and corrosion during idle periods and cools air-tool mechanisms during operation
- Meets the requirements of pneumatic equipment manufacturers

TECHNICAL PROPERTIES

The values listed below are typical of current production. As variations may occur, these numbers do not constitute a specification.

PROPERTIES	TEST METHODS	ISO VISCOSITY GRADE	
		46	100
Kinematic Viscosity cSt @ 40°C	ASTM D445	49.0	109.4
Kinematic Viscosity cSt @ 100°C	ASTM D445	7.4	12.1
Viscosity Index	ASTM D2270	110	100
Pour Point, °C	ASTM D 97	-45°	-30°

PRODUCT SELECTION

Product availability can vary by location. Please contact your local retail co-op for further details.

PRODUCT SIZES	ISO VISCOSITY GRADE	
	46	100
1 L Bottle		
5 L Bottle		
10 L Bottle		
20 L Pail		✓
110 L Drum		
205 L Drum	✓	✓
1000 L Tote		

MATERIAL SAFETY DATA SHEETS

Product-specific material safety data sheets (MSDS) can be obtained by contacting your local retail co-op or Federated Co-operatives Limited (see contact information below) or by going online at coopconnection.ca

RECYCLING OF USED LUBRICANTS AND CONTAINERS

Please protect the environment when disposing of petroleum products. All products should be taken to an authorized collection facility or picked up by a qualified organization. This ensures the products will be disposed of in an environmentally sensitive manner. For additional information on used-oil recycling programs, please see the following:

- Saskatchewan – www.usedoilrecyclingsk.com
- Alberta – www.usedoilrecyclingab.com
- British Columbia – www.bcusedoil.com
- Manitoba – www.usedoilrecycling.com/en/mb

CONTACT INFO

For more information on this or any other CO-OP[®] lubricant product, please contact your local retail co-operative or Federated Co-operatives Limited.

petroadmin@fcl.crs • www.fuel.crs • www.agro.crs

SONIC[®] [®]Registered trademark of Federated Co-operatives Limited, Saskatoon S7K 3M9

[®]CO-OP and the CO-OP logo are registered trademarks of TMC Distributing Ltd., Saskatoon S7K 3M9



**PREMIUM
LUBRICANTS**